

KING TA HAN TECHNOLOGY CO. LTD

E-mail address : kth@kthtw.com

Global Website : http://www.kth-automaticdoor.com

LOCATION : 2F-1,NO.286-8,Sinya Rd .,Cianjhen District, kaohsiung City.80673, Taiwan

AUTOMATIC DOOR SYSTEM SERIES



Registration Number: 8476815113



No restrictions for used places, the best choice for city architectures. With top security device, no misgivings about danger.

Excellent Quality & High-performance.

ТҮРЕ	H-5	
MODEL	SINGLE-WINGED	BI-PARTING
DOOR WEIGHT	250kg X1(DOOR)	200kg X2(DOOR)
DOOR WIDTH	500mm~6000mm	500mm~6000mm
INSTALL WAY	SURFACE INSTALL	SURFACE INSTALL
MOTOR	DC24V 100W BRUSHLESS DC MOTOR	
CONTROL	STANDARD MICRO-CONTROL	
POWER CONSUMPTION	100W	
VOLTAGE	AC100V~240V	
ENVIRONMENTAL TEMPERATURE	-20°C~+50°C	
VOLUME	60 DECIBEL(MAX.)	
STARTING SPEED	600mm/SEC.	550mm/SEC.
STARTING TIMES	0~20 SEC. (REGULABLE)	
TRANSMISSION IMPORTANT CONDITION	RACK BELT S8M	
OPENING DOOR RANGE	FULL/HALF-OPEN (REGULABLE)	
PFC POWER EFFICIENCY	0.95(IN AC100V FULL LOAD)	
TRACTION FORCE	3kg	