

- 2. The balance door can replace the bullet door. The door can be located after opening 90 degrees, which is more convenient when evacuating crowds.
- 3. The opening track of the door is round, and the door will not take up a lot of space when opened.
- 4. The structure is safe, and the risk of door fan dumping and injury caused by the ground falling is significantly reduced.
- 5. The door body is freely assembled and can be installed independently as the entrance of the building, and can also be used in conjunction with the automatic door.
- 6. The surface decoration of the door is diversified, which can meet the requirements of different customers.
- 7. There is no need to groove on the ground, and the on-site construction is relatively simple.

GT-Z BALANCE DOOR

Model	Applicable door weight (kg)	Door width (mm) Single Double open open		The highest door (mm)	Minimum door (mm)
GT-Z5150	150	1100	2200	3000	760
GT-Z5200	200	1250	2500	4000	760
GT-Z5400	400	1500	3000	4500	900
GT-Z5500	500	1800	3600	4800	900

GT-B BALANCE DOOR

	Applicable door weight (kg)	Door width (mm)		The highest door	Minimum door
Model		Single open	Double open	(mm)	(mm)
GT-B5150	150	1100	2200	3000	900
GT-B5300	300	1250	2500	4000	900
GT-B5500	500	1800	3600	4800	900

Nabtesco

Nabco Automatic Door (Beijing) co., Ltd.

2F, Liandong U Valley, no. 15, Jingsheng South Fourth street, majuqiao District, Beijing

Postcode: 101102 Tel: 010-60503958 Fax: 010-60503968



Shanghai Branch

Room 1717, Yuexiu Building, No. 388 Fushan Road, Pudong New District, Shanghai

Postcode: 200122 Tel: 021-33538556 Fax: 021-33536558

Guangzhou Office

Room 1701B, Poly Clovis Zhongying Building, No. 9 Huaqiang Road, Zhujiang New Town, Tianhe District, Guangzhou

Postcode: 510623 Tel: 020-38837824

